

Specification

Specification of 2021-08-13

Measurements		AWP-20s	AWP-25s	Machine
	Working height	8.12 m	9.57 m	
	Platform height	6.12 m	7.57 m	
A	Height - stowed (Standard)	1.98 m	1.98 m	
	Height - stowed (RT/Narrow)	2.01 m	2.01 m	
C	Length - stowed (Standard)	1.24 m	1.31 m	
	Length- stowed (RT/Narrow)	1.60 m	1.60 m	
E/-	Width (Standard / RT / Narrow)	0.74 / 0.76 / 0.56 m	0.74 / 0.76 / 0.56 m	
Productivity				
	Lift capacity	159 kg	159 kg	
	Measurements	Indoor / outdoor	Indoor / outdoor	
F, G	Outrigger footprint (l/w) (Standard)	(1.55/1.35 m) / (2.46/2.26 m)	(1.75/1.55 m) / (2.97/2.79 m)	
	Outrigger footprint (l/w) (RT/Narrow)	(1.80/1.47 m) / (-)	(1.80/1.47 m) / (-)	
H	Corner access (Standard)	0.38 / 0.48 m	0.48 / 0.76 m	
	Corner access (RT/Narrow)	0.53 / -	0.51 / -	
I, J	Wall access front/side (Standard)	(15/33 cm) / (48/81 cm)	(18/43 cm) / (74 cm/1.07 m)	
	Wall access front/side (RT/Narrow)	(30/43 cm) / (-)	(25/43 cm) / (-)	
	Platform Dimensions:	(l/w/h)	(l/w/h)	
	Standard	69 cm/66 cm/1.14 m	69 cm/66 cm/1.14 m	
	Gated standard	69 cm/66 cm/1.14 m	69 cm/66 cm/1.14 m	
	Gated narrow	69 cm/51 cm/1.14 m	69 cm/51 cm/1.14 m	
	Gated ultra-narrow	56 cm/46 cm/1.14 m	56 cm/46 cm/1.14 m	
	Standard fiberglass	74 cm/67 cm/1.10 m	74 cm/67 cm/1.10 m	
Weight				
	AC models (Standard) / (RT/Narrow)	307 / 299 kg	330 / 315 kg	
	DC models (Standard) / (RT/Narrow)	347 / 340 kg	371 / 354 kg	
Power				
	Power source	DC - (12V / 110V / 230V / 50-60 Hz) AC - 110V / 220V / 50-60 Hz		

Specification

Specification of 2021-08-13

Standard Features

- Auxiliary platform lowering
- Most rigid mast in the industry
- Rocker base system for manoeuvrability
- Easily rolls through standard doorways
- AC power to platform (cable only)
- Dual activated up/down switch
- Small outrigger footprints
- Outrigger storage pockets
- Easy loading in pickup trucks
- Tie down attachment points
- Overhead crane attachment point
- Wide forklift pockets
- Rear access forklift pocket
- LED lights confirm proper set-up

Power

- AC power 110V/220V / 50-60 Hz
- DC power with worldwide automatic "smart" charging system (12V / 110V / 230V / 50-60 Hz)

Options & Accessories

- Power to platform: plug, socket, with optional Residual-current Circuit Breaker with Overcurrent protection
- Super Straddle with pin and outrigger interlocks
- Narrow base conversion kit (AWP-20, -25 RT only)
- Different lengths of outriggers (please refer to safety decals for base use in./out. application)
- Outdoor outriggers for AWP Standard base only
- Rough terrain base conversion kit (AWP-20, -25 N only)
- Operational warning light and descent alarm package
- Tool tray (not available on narrow or ultra-narrow platform)
- Fluorescent tube caddy (not available on fiberglass platform)
- Platform locating laser light (not available on fiberglass platform)
- Tilt back frame

